

Programmable 2/3 Channel High-Performance Power Supply HMP2020 / HMP2030

NEW




HMP2030



2 channel derivative
HMP2020



Individual linking of single
channels using FuseLink



Rear outputs for simple
integration in rack systems



- ✓ HMP2020: 1x0...32V/0...10A 1x0...5.5V/0...5A
- ✓ HMP2030: 2x0...32V/0...5A 1x0...5.5V/0...5A
- ✓ 188W output power realized by intelligent power management
- ✓ Low residual ripple: <math>< 150\mu\text{V}_{\text{rms}}</math> due to linear post regulators
- ✓ High setting- and read-back resolution of 1mV/0.1mA
- ✓ Galvanically isolated, earth-free and short circuit protected output channels
- ✓ Advanced parallel- and serial operation via V/I tracking
- ✓ EasyArb function for free definable V/I characteristics
- ✓ FuseLink: individual channel combination of electronic fuses
- ✓ Free adjustable overvoltage protection (OVP) for all outputs
- ✓ All parameters clearly displayed via LCD/glowing buttons
- ✓ Rear connectors for all channels including sense
- ✓ USB/RS-232 Interface, optional Ethernet/USB or IEEE-488

Programmable 2 Channel High Performance Power Supply HMP2020
Programmable 3 Channel High Performance Power Supply HMP2030

All data valid at 23 °C after 30 minute warm-up

Outputs

Advanced parallel and series operation: simultaneously switch on/off of active channels via 'Output' button, common voltage- and current control using tracking mode (individual channel linking), individual mapping of channels which shall be affected by FuseLink overcurrent protection (switch-off), all channels galvanically isolated and independant from protective earth

HMP2020	1 x 0...32V/0...10A	0...5.5V/0...5A
HMP2030	2 x 0...32V/0...5A	0...5.5V/0...5A

Output terminals:	4mm safety sockets frontside Screw-type terminal rear side (4 units per channel)
-------------------	--

Output power:	188W max.
HMP2020/HMP2030	

Compensation of lead resistances (Sense):	1V
---	----

Overvoltage / overcurrent protection (OVP/OCP):	Adjustable for each channel
---	-----------------------------

Electronic fuse:	Adjustable for each channel, combinable via FuseLink
------------------	--

Response time:	< 10ms
----------------	--------

32V channels

Output values:	
HMP2020	1 x 0...32V/0...10A, (5A at 32V, 160W max.)
HMP2030	2 x 0...32V/0...5A, (2.5A at 32V, 80W max.)

Resolution:	
Voltage	1mV
Current HMP2030	< 1A: 0.1mA; ≥ 1A: 1mA
Current HMP2020	< 1A: 0.2mA; ≥ 1A: 1mA

Setting accuracy:	
Voltage	< 0.05% + 5mV (typ. ±2mV)
Current HMP2030	< 0.1% + 5mA (typ. ±0.5mA at I < 500mA)
Current HMP2020	< 0.1% + 5mA (typ. ±1mA at I < 500mA)

Measurement accuracy:	
Voltage	< 0.05% + 2mV
Current HMP2030	< 500mA: < 0.05% + 0.5mA, typ. ±0.2mA
Current HMP2030	≥ 500mA: < 0.05% + 2mA, typ. ±1mA
Current HMP2020	< 500mA: < 0.05% + 0.5mA, typ. ±0.5mA
Current HMP2020	≥ 500mA: < 0.05% + 2mA, typ. ±2mA

Residual ripple (3Hz...100kHz):	
Voltage	< 150µV _{rms}
Current	< 1mA _{rms}

Stabilisation at load change (10...90%):	
Voltage	< 0.01% + 2mV
Current	< 0.01% + 250µA

Stabilisation at line voltage variation (±10%):	
Voltage	< 0.01% + 2mV
Current	< 0.01% + 250µA

Entire load regulation: (at 10%...90% load peak, balance time to match within 10mV U _{nom.})	< 100µs
--	---------

5.5V channel

Output values:	
HMP2020/HMP2030	1 x 0...5.5V/0...5A

Resolution:	
Voltage	1mV
Current	< 1A: 0.1mA; ≥ 1A: 1mA

Setting accuracy:	
Voltage	< 0.05% + 5mV (typ. ±2mV)
Current	< 0.1% + 5mA (typ. ±0.5mA at I < 500mA)

Measurement accuracy:	
Voltage	< 0.05% + 2mV
Current	< 500mA: < 0.05% + 0.5mA; typ. ±0.2mA ≥ 500mA: < 0.05% + 2mA, typ. ±1mA

Residual ripple (3Hz...100kHz):	
Voltage	< 150µV _{rms}
Current	< 1mA _{rms}

Stabilisation at load change (10%...90%):	
Voltage	< 0.01% + 2mV
Current	< 0.01% + 250µA

Stabilisation at line voltage variation (±10%):	
Voltage	< 0.01% + 2mV
Current	< 0.01% + 250µA

Entire load regulation: (at 10%...90% load peak, balance time to match within 10mV U _{Nenn})	< 100µs
--	---------

Arbitrary Function easyARB (32V and 5V channels)

Parameters of points:	Voltage, current, time
Number of points:	128
Dwell time:	10ms ...60s
Repetition rate:	Continuously or burst mode with 1...255 repetitions
Trigger:	Manually via keyboard or via Interface

Maximum ratings

Reverse voltage:	33V max.
Reverse polarized voltage:	0.4V max.
Max. permitted current in case of reverse voltage:	5A max.
Voltage to earth:	150V max.

Miscellaneous

Temperature coefficient/°C:	
Voltage	0.01% + 2mV
Current	0.02% + 3mA

Display:	
HMP2020/HMP2030	240 x 64 Pixel LCD (full grafical)

Memory:	Non volatile memory for 3 Arbitrary functions and 10 device settings
---------	--

Interface:	Dual-Interface USB/RS-232 (HO720)
Process time:	< 50ms

Protection class:	Safety class I (EN61010-1)
Power supply:	115/230V ± 10%; 50/60Hz, CAT II

Mains fuse:	Microfuse 5 x 20mm slow blow
HMP2020/HMP2030	115V: 2 x 6A 230V: 2 x 3.15A

Power consumption:	
HMP2020/HMP2030	350VA max.

Operating temperature:	+5°C...+40°C
Storage temperature:	-20°C...+70°C

Max. rel. humidity:	5%...80% (non condensing)
---------------------	---------------------------

Dimensions (W x H x D):	
HMP2020/HMP2030	285 x 75 x 365mm

Weight:	
HMP2020/HMP2030	8,5kg

Accessories supplied: Line cord, Operating manual, Dual-Interface USB/RS-232 (HO720), CD

Optional accessories:
 HO730 Dual-Interface Ethernet/USB
 HO740 Interface IEEE-488 (GPIB), galvanically isolated
 HZ10S 5 x silicone test lead (measurement connection in black)
 HZ10R 5 x silicone test lead (measurement connection in red)
 HZ10B 5 x silicone test lead (measurement connection in blue)
 HZ42 2RU 19" Rackmount Kit