

## LIGHT METER



### FEATURES

- Wide range for measurements as high as 40000 lux and 4000 fc.
- 0.01 lux and 0.001 fc resolution for accurate low light level measurements.
- Light sensor cover is included for preserving sensor life.
- Auto off function.
- Data hold and peak hold function.
- Low battery indication.
- Over range indication.
- Auto-ranged.
- Manual-ranged.
- Calibration mode is provided.
- 9V battery system.
- Selection key for lux and fc.
- The spectral sensitivity close to CIE photopic curve.
- Ideal tool for workplace, clean-room and computer room light testing.
- Video, photographic, office, classroom, and architectural uses.

### SPECIFICATIONS

Measuring Ranges	39.99 / 399.9 / 3999 / 39990 lx 3.999 / 39.99 / 399.9 / 3999fc
Resolution	0.01 lx - 10 lx 0.001 fc - 1 fc
Accuracy	±(3%rdg+5dgt) Calibrated to standard incandescent lamp, 2856°K.
Display	40000 - conut LCD
Photosensor	Silicon photodiode
Operating / Storage conditions	0°C - 40°C < 80% RH -10°C - 50°C < 70% RH
Power source	9V(6F22.006p)x1 battery
Dimensions	194(L) x 62(W) x 34(D)mm
Weight(prox)	245g(battery is included)
Accessories	Instruction manual Battery Carry case